



- ⊗ Integrated EAS supported
- ⊗ Wide field-of-view, omni-directional scanning capability
- ⊗ Compatible with Linux, Android, Windows XP7/8/10/MAC OS
- ⊗ Stylish, compact design, ideal for a constrained-space environment
- ⊗ Read 1D and 2D barcodes from both paper labels and mobile devices.



Model	NE-5002	Cable	Straight 2.0m
Light Source	Red LED (Lighting) Color Temperature 650nm LED	Mobile tolerance	1m/s
CPU	32bit MIPS @1G Hz	Compatible system	Compatible with Linux, Android, Windows XP7/8/10/MAC OS
Scan Mode	Continue scanning & Automatic induction	Input Voltage	DC 3.6V-5V
Image Size	1280x800 pix	Working current	< 200mA
Scanning speed	60 fps	stand-by current	< 150mA
Decoding Depth	0 – 150mm@ (13mil UPC/EAN 100%,PCS=90%)	Indicator	Tone and Volume adjustable
Mnimum Resolution	≥4mil	Interface	USB-HID, USB-VCP, RS-232
Scanning angle	Deflection 360° Indination ±65° Rotation ±60°	Temperature (Operating)	0°C-50°C
Size	L × W × H:152×152×75(mm)	Temperature (Storage)	-40°C-70°C
Weight	600g	Humidity	5% to 95% (non-condensing)
Case Material	ABS+PC, Flame Retardant Material	Light Levels	0-5000Lux (fluorescence), 0-100,000 Lux (sunlight)
Decoding Capability	1D: UPC, EAN, Code 39 (with full ASCII), Codabar, Code 128, Code 93, Code 11, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, MSI Plessey, GS1 DataBar, etc 2D: PDF417, Data Matrix, QR Code, etc		

Distribuito da:
NORDELETRONICA Srl
 Via Cantù, 36 - 20092 Cinisello Balsamo (MI)
www.nordele.it - info@nordele.it
 Tel: +39 02 6111961