# **PM86**



# EMPOWER YOUR BUSINESS WITH WI-FI 6-FEATURED IN THE TRULY RUGGED MOBILE COMPUTER

# Enhanced performance for heavy business solutions

Maintaining a similar look to its popular predecessor PM85, the PM86 comes with upgraded internals for smoother operations. Powered by a 2.0 GHz octa-core Qualcomm processor and 4 GB/64 GB memory, PM86 runs the latest, intensive solutions on Android 11 smoothly. The 4,080 mAh battery ensures all-day operation, while businesses can choose a 5,800 mAh extended battery for more intensive operation. The dual front-facing speaker invites you to clear communication even in a noisy work environment. The three 1D/2D scan engines have been tested, tuned, and optimized to work seamlessly with PM86 and capture data fast and accurately.

# High-speed yet reliable wireless connection

Wi-Fi 6 technology empowers your workforce with faster, more secure, and more reliable data transfer. The 2x2 MU-

MIMO significantly enhances each access point within the workplace. Optional LTE allows your employees to remain connected and go anywhere they need to.

# Purpose-built features for the enterprise environment

Through a meticulous designing and testing process, the PM86 has been refined to deliver an exceptional user experience. The back cover and the battery now comprise one integrated part, contributing to increased safety and robustness, and offering a simpler on-the-spot replacement process. The BLE Beacon transmits signals for up to 20 days after the device is switched off and even without the main battery, simplifying device management. Enterprise Hot-Swap keeps the screen on during battery replacement and activates the countdown timer for a shutdown.

# Efficiency through backward compatibility and lasting durability

PM86's backward compatibility with PM85 charging cradles<sup>\*</sup> minimizes the cost, while you can still choose a new and improved set of optional accessories including different types of charging cradles, a gun handle with a scan trigger, and a brand-new UHF RFID reader. It is a truly rugged device that withstands multiple drops from 2.0 m (6.6 ft.) to the concrete floor with the Rugged Boot and 1.5 m (5.0 ft.) without, and has IP67 and IP65 rating dust and water resistance, further decreasing the overall downtime and the cost.

# 

android enterprise recommended

# Industries


Field Services Transport & Logistics Warehouse Management Retail Hospitality

# Accessories

Standard AC/DC Power Adaptor Country Plug LCD Protection Film USB-C cable Battery - Standard: 4,080 mAh - Extended: 5,800 mAh Hand Strap

# Optional

Single Slot Cradle (opt. Ethernet) Dual Slot Cradle\*\* \*\*Connect up to 3 Dual Slot Cradles to charge up to 6 devices at a time 4 Slot Battery Charger Gun Handle UHF RFID Reader Rugged Boot PM86 is backward compatible with PM85 charging cradles\*. \*Except battery bay



# PM86

Main processor	
Qualcomm® octa-	core @2.0 GHz
Operating system	2
Google Android (GMS & AOSP)	Android 11 (upgradable to Android 14) FOTA (Firmware Over The Air) update
Memory and stora	ge
RAM/ROM micro SD SIM	4 GB/64 GB (UFS) Supports up to 512 GB using ExFAT file system 2 nano SIM slots
SAM (optional)	2 micro SAM slots
Sensor	Proximity sensor, Light ambient sensor, Accelerometer, Gyro sensor, Digital compass, SAR sensor, Barometer sensor
PHYSICAL C	HARACTERISTICS
Dimensions	
With STD battery	157.5 x 78.0 x 19.6 mm 6.2 x 3.1 x 0.8 in.
With EXT battery	157.5 x 78.0 x 24.2 mm 6.2 x 3.1 x 1.0 in.
Weight	
With STD battery With EXT battery	287.1 g/10.1 oz. 315.1 g/11.1 oz.
Display	5.0" IPS panel (1080 x 1920 pixels), FHD LED backlight Daylight readable (more than 500 nits) Multi-touch capacitive Corning Gorilla Glass
Power	
Standard battery Extended battery Back-up battery	3.8 V, 4,080 mAh Li-ion rechargeable 3.85 V, 5,800 mAh Li-ion rechargeable 3.7 V, 60 mAh (10C), Enterprise Hot-Swap
Key & buttons	
Right Left	Volume, scan Power, scan
Voice and audio	Two built in microphones (noise-canceling) Dual speaker on front side (output max. 100 dB) Receiver and headset Jack (3.5 mm) Bluetooth headset support PTT support
Standard communications	High speed USB 3.0 Type-C POGO 8 pin
Notification	2 x dual LEDs for power and warning indication, vibration, beep

# WIFI SKU: No GNSS Phone SKU: Qualcomm GNSS GNSS receiver support for GPS, A-GPS, GLONASS, Galileo, and

ETTRUNICA mobile solutions

Beidou

# WIRELESS Wireless WAN EDGE/GPRS/GSM 900/1800/850/1900 B1/2/4/5/6/8/19 B1/2/3/4/5/7/8/12/13/17/19/20/25/26/28 /66 B38/39/40/41 Wireless LAN IEEE 802.11 a/b/g/n/ac/ax/d/h/i/k/r/v, 2x2 MU-MIMO, CCX v4 5 GHz: 802.11 a/n/ac/ax up to 1200 Mbps 2.4 GHz: 802.11 b/g/n/ax up to 286.8 Mbps 1 to 13 (2412~2472 MHz) 36 to 165 (5180~5825 MHz) 20, 40, 80 MHz WEP/WPA/WPA2 Personal (TKIP/AES), WPA/WPA2 Enterprise (TKIP/AES), WPA3 Personal (SAE), WPA3 Enterprise (AES), WPA3 Enterprise 192-bit mode (GCMP 256), Enhanced Open (OWE), PEAP (MSCHAPV2, GTC), TLS, TTLS (PAP, MSCHAP, MSCHAPV2, GTC), PWD, SIM, AKA, AKA', LEAP CCKM, 802.11r Wireless PAN Bluetooth Class I Ver. 5.0 BLE support Beacon (transmits signals for up to 20 days, power-off and without main battery)

# DATA CAPTURE

#### Integrated scan engine options

N3603, N6703, N6803 FR all support 1D/2D barcode symbologies

#### Camera

WCDMA

LTE FDD

LTE TDD

Radio

Data rates

Operating

bandwidth

Security and

encryption

Fast Roam

Bluetooth

channels Channel

Front	5 MP (optional)
Rear	13 MP with LED flash, F. No. 2.0, Phase Detection Auto Focus (PDAF)

NFC (Near Field Communication)


NFC-Forum (NFC-IP Modes)	Reader for NFC Forum (Tag Types 1 to 5), P2P Active (106 to 424 kbps) Initiator and Target, P2P Passive (106 to 424 kbps) Initiator and Target
Reader (PCD – VCD)	ISO/IEC 14443 A, ISO/IEC 14443 B, ISO/IEC 15693, Mifare Classic 1K/4K, Mifare DESFire, Mifare UltraLight©, Sony FeliCa
UHF Passive RFID	tag integrated for device tracking

# USER ENVIRONMENT

Operating temperature	-20 °C to 60 °C/-4 °F to 140 °F
Storage temperature	-25 °C to 70 °C/-13 °F to 158 °F
	1940arded 155 225

Humidity 95% non-condensing

Nordelettronica S.R.L.





Drop	2.0 m (6.6 ft.) with Rugged Boot and
	1.5 m (5 ft.) without, multiple drops to
	concrete across operating temperature
	range, MIL-STD-810H
	1.8 m (6 ft.) multiple drops to concrete at
	room temperature, MIL-STD-810H
Tumble	1,000 cycles, 1 m (3.3 ft.) tumbles per
	IEC 60068-2-31 specification
Rain/dust proof	IP67 and IP65
(Sealing)	
Electrostatic	± 15 kV air discharge
discharge	± 8 kV contact discharge

### **REGULATORY APPROVALS AND** COMPLIANCE

RCM, CE/CB, WPC, BIS, KC, IC, FCC, NRCan, UKCA, NBTC, IFITEL, NOM, CU, FAC, EAC RoHS, FSS, RoHS, WEEE, REACH

# ENTERPRISE SOLUTION



Simple yet powerful management solution

PMDM is a mobile device management solution for managing and monitoring your Point Mobile Android devices.

Centralized management of enterprise devices is vital for better productivity. You should provide a device configuration that the workers can concentrate on their work with the device, and also decrease the device downtime by predicting when to replace the battery, etc.



The EmKit<sup>™</sup> is Point Mobile's value-added service kit engineered for the pure benefit of system integrators. EmKit supports the utilization, solution development, and secure management of your business devices.

# **PULS - ANDROID UPDATE & SECURITY**

PULS is a Point Mobile's lifetime solution, which extends the life cycle of Android-based Point Mobile enterprise devices to up to seven years after a product launch.



Patches, updates & Lifetime Support

Stay up-to-date with the latest updates for 7 years PULS comes free of charge for security patches & updates Get the latest Android version and its newest features Conveniently update yoru devices in the field by FOTA

For further information, please visit www.pointmobile.com or contact your regional sales representative.

# WARRANTY

Subject to the Terms and Conditions, PM86 carries 1 (one) year-warranty period from the date of purchase against the defective materials and manufacturing defects.

For the further inquiry, please contact: service@pointmobile.com

