


SPP-L310

3 inch Mobile Label Printer




Small and Lightweight



Compatible with



Made for iPod iPhone iPad



Detachable Media Holder

Exceptional Performance

- Fully compatible with market-leading programming languages
- Interchange programming language without setting the mode
- Fast data processing and printing speed up to 5 ips (127 mm/sec)
- Standard media width: 80 mm
- Optional media widths with detachable media holder: 58/62/66/70/74 mm



The Perfect Fit for Mobile Environment

- Connectivity options including Bluetooth 4.1 (MFi certified) and Dual-band WLAN (2.4GHz and 5GHz), USB and Serial
- Compatible with all major operating systems including Android™, iOS™ and Windows®
- Supports Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- Smart Wi-Fi setting via mobile devices available



Optimized for Field Operation

- Super compact and light-weight (385g) yet powerful
- 1.8 m / 6 ft. drop rate
- IP54 water and dust proof
- Various accessories and connectivity ports
- Supports transmissive gap sensor and black mark reflective sensor



SPP-L310

3 inch Mobile Label Printer

8x
N°1 MOBILE
RECEIPT
PRINTER
MANUFACTURER



Reported by
Chunichisha

Specifications

Printer Specifications

Print Method

Direct Thermal

Print Speed

Up to 5 ips (127 mm/sec - Label)
Up to 4 ips (102 mm/sec - Linerless)
12.5% pattern

Print Resolution

203 dpi

Print Width

Up to 72 mm

Sensing

Paper End
Gap
Black Mark
Paper Cover Open

Media Characteristics

Media Type

Liner, Linerless (Optional)

Media Width

80 mm
Optional 58 / 62 / 66 / 70 / 74 mm

Media Roll Diameter

Up to 49 mm

Media Thickness

0.07 ~ 0.19mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (W x L x H)

105 x 126 x 58 mm
(4.14 x 4.97 x 2.29 inch)

Weight

Including battery: 385 g (0.85 lbs.)
Paper: 133 g (0.29 lbs.)

Electrical

7.3 V Li-ion, 2850 mAh (Nominal),
Rechargeable Charging time: Up to 4 hrs
EnergyStar Certified

Performance Characteristics

Memory

128 MB SDRAM, 256 MB Flash
256 MB SDRAM, 512 MB Flash (Optional)

Interface

Standard: USB V2.0 HS + Serial
Optional: USB V2.0 HS + Serial + Bluetooth /
WLAN

Bluetooth: V4.1 Classic & LE

WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc,
Wi-Fi Direct, SoftAP)
- WEP40/104, WPA1/2 (PSK, EAP)

* Easy Bluetooth Pairing™ via NFC

Environment Characteristics

Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)
Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity

Operating: 10 ~ 80% RH

Sealing

IP54

Drop Rate

1.8 m (6 ft.)

Software

Emulation

SLCS, BPL-Z™, BPL-C™

Driver / Utility

Windows Driver (Europlus / Seagull),
Linux / Mac CUPS Driver, Virtual COM USB Driver,
Utility Program, LabelArtist-II™, Bartender UL,
OPOS / JPOS Driver, SAP® Device Driver,
Network Auto Installer

SDK / Plugin

Android / iOS / Windows SDK, Linux SDK,
Chrome SDK, Xamarin SDK, Cordova Plugin

Application

Label Artist™ Mobile (Android, iOS)
mPrint App (iOS)

Fonts / Graphics / Symbologies

Fonts

10 SLCS / One SLCS / 16 BPL-Z™ / One BPL-Z™ /
7 BPL-C™ / 23 Code Page / Unicode supported
(UTF-8, UTF-16LE, UTF-16BE)

Graphics

Supporting user-defined fonts, graphics,
formats, layouts and logos

Barcode Symbologies

1D: Codabar, Code 11, Code 39, Code 93,
Code 128, EAN-13, EAN-8, Industrial 2-of-5,
Interleaved 2-of-5, Logmars, MSI, Plessey,
Postnet, GS1 DataBar (RSS-14),
Standard 2-of-5, UPC / EAN extensions,
UPC-A, UPC-E, IMB
2D: Aztec, Codablock, Code 49, Data Matrix,
MaxiCode, MicroPDF417, PDF417,
QR code, TLC 39

Accessories

Standard

Belt Clip, Battery Pack, Battery Charger,
Power Cord

Optional

Belt Strap, Shoulder Strap, Single Battery Cradle,
Quad Battery Charger, Vehicle Charger,
Serial / USB Cable, Vehicle-Holder,
RAM mount Vehicle-Holder, Case,
Protective Case, Detachable Media Holder

Supplies

Compatible with B-linerless™ BIXOLON's flexible
and ecological linerless label consumables