

# SPP-L410

4 inch Mobile Label Printer



Ticketing



Healthcare



Logistics



Retail

## Compact yet Rugged



### Productivity Enhancing Performance

- Fully compatible with market-leading programming languages
- Extensive memory up to 256 MB SDRAM, 512 MB Flash
- Fast data processing and printing speed up to 4 ips (102 mm/sec)
- Supports gap, Black Mark, paper cover open sensor (Fixed Transmissive Sensors)



### Reliable Printing on the Move

- Connectivity options including Bluetooth® and Dual-band Wireless Lan (2.4GHz and 5GHz), USB and Serial
- Compatible with all major operating systems including Android™, iOS™ and Windows®
- Supports Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- Smart Wi-Fi setting via mobile devices



### Rugged and Easy to Carry

- Smallest in its class (143x138x66 mm)
- Ergonomic and lightweight (530 g)
- 1.8 m / 6 ft. drop rate
- Resistance to water and dust (IP54)
- Various accessories and connectivity ports

# SPP-L410

4 inch Mobile Label Printer

9x **N°1** MOBILE RECEIPT PRINTER MANUFACTURER

## Specifications

Reported by  
Chunichisha



### Printer Specifications

#### Print Method

Direct Thermal

#### Print Speed

Up to 4 ips (102 mm/sec - Liner)  
Up to 3 ips (76 mm/sec - Linerless)

#### Print Resolution

203 dpi

#### Print Width

Up to 104 mm

#### Sensing

Paper End  
Gap  
Black Mark  
Paper Cover Open

### Media Characteristics

#### Media Type

Liner, Linerless (Optional)

#### Media Width

112 mm / 105 mm (Optional)

#### Media Roll Diameter

Up to 56 mm

#### Media Thickness

0.07 ~ 0.19 mm

#### Supply Method

Easy Paper Loading

### Physical Characteristics

#### Dimensions (WxDxH)

143 x 138 x 66 mm  
(5.63 x 5.44 x 2.60 inch)

#### Weight

Including battery: 530 g (1.17 lbs.)  
Paper: 242 g (0.53 lbs.)

#### Electrical

7.3V Li-ion, 2850 mAh (Nominal),  
Rechargeable Charging time: Up to 4 hrs  
EnergyStar Certified

### Performance Characteristics

#### Memory

128 MB SDRAM, 256 MB Flash  
256 MB SDRAM, 512 MB Flash (Optional)

#### Interface

Standard: USB V2.0 HS + Serial  
Optional: USB V2.0 HS + Serial + Bluetooth / WLAN

WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc,  
Wi-Fi Direct, SoftAP)  
- WEP40/104, WPA1/2 (PSK, EAP)

Easy Bluetooth Pairing™ via NFC

### Environment Characteristics

#### Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)  
Storage: -30 ~ 70°C (-22 ~ 158°F)

#### Humidity

Operating: 10 ~ 80% RH

#### Sealing

IP54

#### Drop Rate

1.8 m (6 ft.)

### Software

#### Emulation

SLCS, BPL-Z™, BPL-C™

#### Driver / Utility

Windows Driver (Europlus/Seagull),  
Linux/Mac CUPS Driver, Virtual COM USB Driver,  
Utility Program, Label Artist-II™, Bartender UL,  
OPOS/JPOS Driver, SAP® Device Driver,  
Network Auto Installer

#### SDK / Plugin

Android/iOS/Windows SDK, Linux SDK,  
Chrome SDK, Xamarin SDK, Cordova Plugin

#### Application

Label Artist™ Mobile (Android, iOS),  
mPrint App (Android, iOS)

### Fonts / Graphics / Symbologies

#### Fonts

Bitmap Fonts (10 SLCS™, 16 BPL-Z™, 7 BPL-C™),  
Scalable Fonts (1 SLCS™, 1 BPL-Z™),  
23 Code page,  
Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

#### Graphics

Supporting user-defined fonts, graphics,  
formats, layouts and logos

#### Barcode Symbologies

1D: Codabar, Code 11, Code 39, Code 93,  
Code 128, EAN-13, EAN-8, Industrial 2-of-5,  
Interleaved 2-of-5, Logmars, MSI, Plessey,  
Postnet, GS1 DataBar (RSS-14),  
Standard 2-of-5, UPC/EAN extensions,  
UPC-A, UPC-E, IMB  
2D: Aztec, Codablock, Code 49, Data Matrix,  
MaxiCode, MicroPDF417, PDF417, QR code,  
TLC 39

### Accessories

#### Standard Accessories

Belt Clip, Battery, Battery Charger, Power Cord

#### Optional Accessories

Belt Strap, Shoulder Strap, Single Battery Cradle,  
Quad Battery Charger, Vehicle Charger,  
Serial/USB Cable,  
RAM Mount Vehicle Holder, Case

### Supplies

Compatible with B-linerless™ BIXOLON's flexible  
and ecological linerless label consumables



Made for  
iPod iPhone iPad  
Android Windows