# **SPP-R310**

3 inch Mobile Printer









Food

Deliveries

Retail



service

# Compact and Ergonomic





#### **Smaller and Lighter Design**

- Easy to grip: 30% lighter and 26% slimmer than SPP-R300
- One touch cover open and easy paper loading









#### **Mobile Field-Work Optimization**

- Wireless and wired connectivity options including Bluetooth, WiFi, USB and Serial
- Supporting Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- Dual-band WLAN (5GHz and 2.4 GHz)
- Dual-mode Bluetooth V4.1 Classic (MFi AP2 certified) and LE
- IP54 (Printer only) water and dust proof
- 1.8 m / 6 ft. drop rate
- Long-lasting battery life (24-hour stand by



#### **Built for Multi-Purpose**

- Fast printing speed up to 100 mm/sec (Receipt)
- Designed for the receipt and label printing (Simple to switch via the feed button)
- Optional linerless label printing (80 mm/sec at 203dpi)
- Supports black mark reflective sensor and transmissive gap sensor (Optional Positioning)



# SPP-R310

## 3 inch Mobile Printer













## **Specifications**

#### **Printer Specifications**

#### **Print Method**

Direct Thermal

#### **Print Speed**

Up to 100 mm/sec (Receipt) Up to 80 mm/sec (Linerless) 12.5% pattern

#### **Print Resolution**

203 dpi

#### **Print Width**

Up to 72 mm

#### Sensor

Paper End Paper Cover Open Black Mark (Optional positioning) Gap (Optional)

#### Media Characteristics

#### Media Type

Receipt, Label and Linerless (Optional)

#### Media Width

80 mm

#### Media Roll Diameter

Up to 50 mm

#### **Media Thickness**

 $0.07 \pm 0.005 \, \text{mm}$ 

#### Supply Method

Easy paper loading

#### Physical Characteristics

#### Dimensions (WxDxH)

105.0 x 126.0 x 58.0 mm (4.14 x 4.97 x 2.29 inch)

#### Weight

Including battery: 385 g (0.85 lbs.) Including MSR: 405 g (0.9 lbs.) Paper: 133 g (0.29 lbs.)

#### Electrical

7.3 V Li-ion, 2600 mAh, Rechargeable Charging time: Up to 4.0 hrs EnergyStar Certified

#### Performance Characteristics

#### Memory

8 MB SDRAM, 4 MB Flash

#### Interface

Standard: USB V2.0 FS + Serial Optional: USB V2.0 FS + Serial + Bluetooth1 / WI AN2

SPP-R310plus:

USB V2.0 FS + Serial + Bluetooth3 / WLAN4

Bluetooth1: V3.0 + EDR

WLAN2: 802.11b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct) - WEP40/104, WPA1/2 (PSK, EAP)

Bluetooth3: V4.1 (Classic + LE)

WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)

#### **Environment Characteristics**

#### Temperature

Operating: -15 ~ 50°C (5 ~ 122°F) Storage: -30 ~ 70°C (-22 ~ 158°F)

### Humidity

Operating: 10 ~ 80% RH

## Sealing

IP54

#### **Drop Rate**

1.8 m (6 ft.)

#### Software

#### **Emulation**

BXL / POS

#### Driver / Utility

Windows Driver, OPOS / JPOS Driver, Linux / Mac CUPS Driver, Utility Program

#### SDK / Plugin

Android / iOS / Windows SDK, Linux SDK, Xamarin SDK, Chrome SDK, Cordova Plugin

#### Application

mPrint App (iOS), mPrint Server (Windows, iOS)

BIXOLON Profile Manager XPM™, XCM™ (Windows, Android)

#### Fonts / Graphics / Symbologies

#### **Character Size**

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24 KOR, CHN: 24 x 24

#### Characters Per Line

Font A: 48 Font B, C: 64 KOR, CHN: 24

#### **Character Sets**

Alphanumeric: 95 Expanded Graphics: 128 x 33 page International: 32 Optional Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

#### Graphics

Supporting user-defined fonts, graphics, formats, layouts, and logos

#### **Barcode Symbologies**

1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Aztec, Data Matrix, GS1 Databar, MaxiCode, PDF417, QR code

#### Accessories

#### Standard Accessories

Belt Clip, Battery Pack, Battery Charger, Power Cord, Paper

#### **Optional Accessories**

Belt Strap, Case, Protective Case, Shoulder Strap, Single Battery Cradle, Quad Battery Charger, Cigarette Lighter Charger, Vehicle Holder, Serial / USB Cable

#### **Integrated Card Reader (Optional)**

3 Track (T-DES / DUKPT (Optional))

#### Supplies

B-linerless™: BIXOLON's flexible and ecological linerless label consumables





Via Cantù, 36 - 20092 - Cinisello Balsamo (MI) - Italia +39 02 6111961 - www.nordele.it - info@nordele.it







<sup>\*</sup> Easy Bluetooth Pairing™ via NFC