

Powerful 8-Inch Rugged Tablet for Business

Janam's HT1 exceeds enterprise expectations – delivering the most powerful and advanced 8-inch rugged tablet for retail, warehousing, manufacturing, field service, fleet-based operations and other demanding work environments. Purpose-built to help organizations achieve maximum productivity, the HT1 combines an exceptionally sleek and lightweight design with an abundance of first-rate features to foster more collaboration across the supply chain.

Powered by Android 9 (Pie) with Google Mobile Services (GMS), Janam's HT1 rugged tablet provides unparalleled ease-of-use and is guaranteed to meet the strictest enterprise requirements. HT1 is easily deployed, scaled and supported across businesses of all types and sizes. A high-capacity, swappable battery, along with intuitive power management tools and an energy-efficient processor, ensures uninterrupted performance in extended-shift work environments. Wi-Fi, Bluetooth, NFC and 4G LTE connectivity allow factory and warehouse workers, field service technicians, police officers, nurses and airline personnel, among others, to access business-critical information anywhere their job takes them.

Winning Features:

- Ergonomically designed for one-handed use
- Android 9 with Google Mobile Services (GMS)
- Bright 8-inch touch screen optimized for indoor/outdoor applications
- Military-grade certified ruggedness
- IP67 sealing

- Blazing-fast Snapdragon octa-core processor
- Superior 1D/2D barcode scanning (optional)
- NFC reading capabilities
- Wi-Fi, Bluetooth, 4G LTE
- 8200mAh hot-swappable battery
- Standard 2-year warranty











An optional 2D imager module is easily attached to the HT1 to provide high-performance scanning of printed and mobile barcodes, while high-resolution front and rear cameras enable mobile workers to conduct video calls, record proof-of-delivery and scan documents.

The rugged HT1 is as sleek and stylish as a consumer tablet, but can survive extreme heat, icy conditions, repeated drops to concrete and is sealed against the ingress of dust and immersion in up to three feet of water, delivering extended lifecycle and maximum return-on-investment to enterprise customers.



























HT1 Specifications

Operating System	Android 9 (Pie) with Google Mobile	
operating system	Services (GMS)	
Processor	2.0 GHz Qualcomm	
	Snapdragon™ 625 octa-core	
Memory	4GB LPDDR3 RAM/64GM eMMC Flash	
Expansion	User-accessible microSD card slot	
	with SDXC support; SIM slot	
Power	8200mAh 3.8V swappable,	
	rechargeable Li-ion battery	
PHYSICAL		
20 D	0.0511	

PHYSICAL	
Dimension	9.25" L x 5.74" W x .57" D / 235mm L x 146mm W x 14.5mm D
Weight	22.7oz / 645g including battery
Display	8.0" HD with Corning® Gorilla® Glass 3; 400+ nits
Touch Panel	Capacitive touch screen

ENVIRONMENTAL	
Operating Temperature	-4º to 131º F / -20º to 55º C
Storage Temperature	-40° to 158° F / -40° to 70° C
Humidity	Non-condensing, 95%
Drop	Multiple 4ft / 1.2m drops to concrete per MIL-STD-810G and MIL-STD-810F
Water & Dust	IP67
Electro Static Discharge (ESD)	+/- 15kV air; +/- 8kV contact

INTERFACE FEATURES		
Audio	3.5mm headset jack; 2 speakers; microphone	
Alerts	Vibration; LED indicators	
Connectors	USB-C; Pogo Pin industrial connector	
LED Indicators	Dual-color	
Motion Sensor	Accelerometer; Light Sensor; Proximity Sensor; Digital Compass	
External Buttons	8 hard keys	

DATA CAPTURE	
Imager	High-performance 1D/2D imager (optional)
Camera	13MP color rear-facing autofocus camera with user-controllable LED flash and 5MP front-facing camera
NFC	Reads ISO14443 Type A; ISO14443 Type B; IEC15693

WWAN	GSM: 850/900/1800/1900
	TD-SCDMA: B34/39
	WCDMA: B1/2/5/8
	CDMA/EVDO: BC0
	LTE FDD: B1/2/3/4/5/7/8/12/13/17/20/25/28
	LTE TDD: B38/B39/B40/41
WLAN	802.11a/b/g/n/ac
Security	IEEE 802.11n; WEP; WPA/WPA2 Personal
	(TKIP. AES); WPA/WPA2 Enterprise (TKIP, AES
	PEAP(MSCHAPv2, GTC): TLS; TTLS
	(PAP, MSCHAP, MSCHAPv2, GTC); PWD; SIM
	AKA; AKA', LEAP
WPAN	Bluetooth Class I 4.1 (BLE)
GPS	GPS supports GLONASS

ACCESSORIES	
Desktop Charging Cradle Kit	
Handstrap	N. Carlotte
Vehicle Cradle	

DRY	
IEC60529:2013; IEC68-2-32:1990;	
GB4208-2008; GB/T2423.8-1995	
FCC; CE; IC; RCM; MIL-STD-461F	
RoHS; REACH and WEEE compliant	



Nordelettronica S.R.L.

Via Cantù, 36 - 20092 - Cinisello Balsamo (MI) - Italia +39 02 6111961 - www.nordele.it - info@nordele.it





